




# BLEND & RECLAIM

## GH AND GH-M SERIES WEIGH HOPPERS



### GH-M SERIES EXTRUDER MONITOR UNIT

The GH extrusion control and GH-M extruder rate monitor units match the extruder throughput, track material usage, and can control extruder output with the optional control system.



### STANDARD FEATURES

- Surge hopper with refill valve
- Mass flow weigh hopper design for first in/first out material flow eliminates segregation
- Weigh hopper with sight glass for visual check
- High accuracy, precision cantilever load cell
- Allen-Bradley remote control system with monochrome touch-screen
- Material inventory
- Line footage inventory
- Line and screw speed pickup
- DF-1 communications port (Ethernet optional)
- Haul-off or extruder speed control software included; specify at time of order
- Weight per length control to  $\pm 1/2\%$  of maximum extruder rate
- Serial printer port connection
- Hopper lid arranged for AEC receivers and loaders
- 115/1/60 supply voltage
- Weight per area control available

### OPTIONS

- Additional speed potentiometer
- Speed adjust module
- Lid for non-AEC loader/receiver



1100 E Woodfield Road, Suite 588  
Schaumburg, IL 60173 USA  
Tel. 847-273-7700 Fax 847-273-7804

[www.aecinternet.com](http://www.aecinternet.com)



**WHITLOCK/  
MATERIAL  
HANDLING**



**HEAT & COOL**



**BLEND &  
RECLAIM**



**NELMOR/  
GRANULATE**



**DOWNSTREAM  
EXTRUSION**



**AUTOMATE**



**SYSTEMS  
CONTRACTING**



**SERVICE**




# BLEND & RECLAIM

## GH-F SERIES GRAVIMETRIC FEEDER



### GH-F SERIES GRAVIMETRIC FEEDER

The GH-F Series gravimetric feeder adds colorant or other free-flowing material to your process, based on a self-calibrating controller that makes recalibration unnecessary and eliminates the overfeeding that typically accompanies volumetric feeders.



### STANDARD FEATURES

- Precision 0.02% span accurate weighing system
- Serial printer port
- Aluminum and mild steel contact surfaces
- DF-1 communications port (Ethernet optional)
- Field-mounted proximity switch for extruder speed pick-up
- Surge hopper with reload valve
- Square mounting flange for machine-mount
- Allen-Bradley remote control system with monochrome touch-screen
- 3" (76mm) OD discharge opening
- Extruder following circuit
- Hopper lid arranged for AEC receivers and loaders
- 115/1/60 supply voltage

### OPTIONS

- Customer-specified mounting flange
- Special voltage (transformer)
- Supply hopper lids cut for other vacuum receivers or loaders; cut-out pattern only<sup>1</sup>

<sup>1</sup> Allow additional delivery lead times



1100 E Woodfield Road, Suite 588  
Schaumburg, IL 60173 USA  
Tel. 847-273-7700 Fax 847-273-7804



**WHITLOCK/  
MATERIAL  
HANDLING**



**HEAT & COOL**



**BLEND &  
RECLAIM**



**NELMOR/  
GRANULATE**



**DOWNSTREAM  
EXTRUSION**



**AUTOMATE**



**SYSTEMS  
CONTRACTING**



**SERVICE**