



NELMOR-GRANULATE

GP2000 SERIES CENTRAL GRANULATOR



GP2042 AND GP2062 SERIES

Featuring Twinshear knife configuration to increase cutting efficiency, the GP2042 and 2062 Series granulators offer throughputs from 1800 lbs./hr up to 2600 lbs./hr. The granulators are easy to maintain, with a drop-down screen cradle and hydraulic tilt mechanism on the infeed hopper for quick and easy access to the cutting chamber and rotor. The 2042/2062 Series' low feed height and large widths are ideal for thermoforming, and a variety of infeed, discharge, and rotor options provide added flexibility for almost any application.

STANDARD FEATURES

- Hand-feed hopper, double wall construction, 70" feed height
- Offset cutting chamber, 2 Twinshear™ bed knives, top access: single edge, HCHC
- 3-knife Twinshear™, steep angle rotor with extended shaft for optional flywheel
- Steep angle, 55 degree, landed HCHC rotor knives
- 75 HP, V belt drive, 450 RPM
- 8" airveyor discharge chute (10" on model GP2062)

OPTIONS

- Feed roll/paddle wheel, sheet feed or side feed
- Modular conveyor feed add-on chute: 88" feed height
- Wear-resistant cutting chamber and rotor
- 3-knife high shear, 5-knife steep angle, or 5-knife high shear rotor (all Twinshear™)
- Steep angle, keen edge HCHC high shear, HCHC rotor knives
- Sound enclosure



1100 E Woodfield Road
Schaumburg, IL 60173 USA
Tel. 847-273-7700 Fax 847-273-7804

www.aecinternet.com



**WHITLOCK/
MATERIAL
HANDLING**



HEAT & COOL



**BLEND &
RECLAIM**



**NELMOR/
GRANULATE**



**DOWNSTREAM
EXTRUSION**



AUTOMATE



**SYSTEMS
CONTRACTING**



SERVICE



NELMOR-GRANULATE

GP2000 SERIES CENTRAL GRANULATOR



A drop down screen cradle provides quick screen access for simplified maintenance



Hydraulic tilt mechanism for the infeed hopper provides complete access to the cutting chamber and rotor.



Twinshear™ knife configuration increases cutting efficiency



Low feed height and large widths are ideal for thermoforming

ADDITIONAL OPTIONS

- 50 HP, 60 HP, 100 HP
- 10" airveyor discharge chute
- Dual flywheel drive
- Variety of screen sizes available
- NEMA 12, 110 volt controls with safety interlocks. Free standing control panel with 460V service
- Other voltages
- #8 or #10 floor mtg. blower, cyclone, cyclone stand, infeed conveyor

	Cutting Chamber Size	Throughput
GP2042	20" x 42"	1800 lbs/hr
GP2062	20" x 62"	2600 lbs/hr



1100 E Woodfield Road
Schaumburg, IL 60173 USA
Tel. 847-273-7700 Fax 847-273-7804

www.aecinertnet.com



**WHITLOCK/
MATERIAL
HANDLING**



HEAT & COOL



**BLEND &
RECLAIM**



**NELMOR/
GRANULATE**



**DOWNSTREAM
EXTRUSION**



AUTOMATE



**SYSTEMS
CONTRACTING**



SERVICE