



GP1600 PREMIER SERIES GRANULATORS

The GP1600 Premier Series granulators offer a wide range of capabilities to handle the most demanding injection molding, blow molding and extrusion requirements. GP1600 models include 16x20, 16x28 and 16x40, providing excellent quality regrind and quiet operation. Unique machined, bolted and doweled construction ensures durability. Double-sealed bearings are lubricated for life. Rotating end discs are standard throughout the Premier Series line for minimized friction and heat buildup.



GP1600 Premier Series Granulator

STANDARD FEATURES

- *Pivoting hopper, drop-down removable screen cradle and machined, bolted cutting chamber simplifies cleaning and maintenance*
- *Low-profile, sound-attenuated infeed systems for robot, hand or conveyor feed applications*
- *HCHC knives manufactured in-house utilizing AEC's proprietary process for heat treating ensures durability and long life*
- *Oversized solid flywheel*

OPTIONAL FEATURES

- *Motor: 25, 30 or 40 HP TEFC motors*
- *Infeed: Sheet/profile/pipe/feed rolls*
- *Rotor: 5 knife, 3 and 5 knife with knife carriers*
- *Discharge: 1.25", 1.5", 2" or 2.5" vacuum takeoff, 4" or 5" pneumatic, bin discharge available on model 1620 only*
- *Knives: D2 components and wear-resistant package*
- *Base: Caster-mounted*
- *Abrasion-resistant cutting chamber and rotor*

GP1600 PREMIER SERIES GRANULATORS

GRANULATE

SPECIFICATIONS

Specifications			
Model	GP1620	GP1628	GP1640
Cutting Circle	16.54" (420.1 mm), 437 rotor RPM		
Throughput	900 lbs/hr (408.2 kg/hr)	1500 lbs/hr (680.4 kg/hr)	1800 lbs/hr (818 kg/hr)
Cutting Chamber	16" x 20" (406.4 mm x 508 mm)	16" x 28" (406.4 mm x 711.2 mm)	16" x 40" (406.4 mm X 1016 mm)
Rotor Knives	3 knife open scooped with rotating end discs (knife carriers and 5-bladerotor optional)		
Discharge	6" pneumatic		8" pneumatic
Motor	20 HP (15 kW) TEFC motor standard, 230/460 VAC		30 HP (23KW) TEFC motor standard 230/460 VAC
Drive Parts	Flywheel/rotor (solid), drive belts, taper lock bearings, and adjustable motor base		
Base	Totally enclosed for sound control, stationary with vibration pad		
Electrical Components	Start/stop push button, complete set of safety interlocks		
Controls	NEMA Type 12		
Feed Height	56.27" (1429.3 mm)		
Overall Height	79.99" (2031.7 mm)		
Overall Length	71.18" (1808 mm)		
Overall Width (A)	51.25" (1301.8 mm)	59.25" (1505 mm)	71.25" (1809 mm)
Weight	3025 lbs. (1372 kg)	3400 lbs. (1542.3 kg)	4000 lbs. (1818 kg)

DIMENSIONS

